



NOTES:

- 1) MATERIAL: 7075-T6/T62/T651 ALUMINUM PLATE
PER QQ-A-250/12 OR AMS-QQ-A-250/13 OR AMS 4045 OR ASTM B209
OR
7075-T6/T62/T651 ALCLAD ALUMINUM PLATE
PER QQ-A-250/13 OR AMS-QQ-A-250/13 OR AMS 4048 / 4049 OR ASTM B209
REF. DART SPEC M7075T6S
- 2) FINISH: HARD ANODIZE IAW MIL-A-8625F TYPE III, CLASS 2, COLOR BLACK
PRIME IAW MIL-P-23377J TYPE I CLASS N; 1-2; 1-2 MIL MAX, AS PER QSI 005
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D5503-1" TAI P/N "RC95T400400VN", REVISION,
BATCH NUMBER AND MANUFACTURE DATE PER QSI 044 METHOD 6-2
- 7) WEIGHT: 0.57 lbs (0.25 kgs)
- 8) ALL NON-DIMENSIONED FEATURES PER CAD FILE D5503-1a.STEP

PRELIMINARY ISSUE

A	NEW ISSUE	JMH	17.07.19
REV.	DESCRIPTION	BY	DATE
DESIGN	JMH	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	SC		
CHECKED	WM	DRAWING NO.	REV. A6
MFG. APPR.	JFS	D5503	SHEET 1 OF 2
APPROVED		TITLE	SCALE
DE APPR.		WIPER POST DEFLECTOR	NTS
DATE	17.07.19	COPYRIGHT © 2017 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

